



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	1 of 21
Revision:	V1.10	Confidential:	Internal Documentation

---

## MEITRACK® GPRS/SMS PROTOCOL

### Document

File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	2 of 21
Revision:	V1.10	Confidential:	Internal Documentation

## Table of Contents

I.	Command Format .....	3
1.	GPRS Format .....	3
2.	SMS Format .....	3
II.	Command List .....	4
III.	Command Details .....	5
1.	Track on Demand (SMS) – A00 .....	5
2.	Track on Demand – Google Map (SMS) – A01 .....	5
3.	Track by Time Interval (SMS) – A02 .....	5
4.	Track on Demand (GPRS) – A10 .....	6
5.	Set Heartbeat Interval (GPRS) – A11 .....	6
6.	Track by Time Interval (GPRS) – A12 .....	6
7.	Heading Change Report (GPRS) – A13 .....	7
8.	Track by Distance Interval – A14 .....	7
9.	Set GPRS – A21 .....	7
10.	Set DNS Server IP – A22 .....	8
11.	Set Secondary GPRS Server – A23 .....	8
12.	Auto Event Report – AAA .....	8
13.	Delete GPRS Event in Queue Buffer – AFF .....	9
14.	Get Authorized Phone Number and SMS Event Flag – B00 .....	9
15.	Authorize Phone Number and SMS Event Flag – B01 .....	9
16.	Add SMS Event Flag to Authorized Phone Number – B02 .....	10
17.	Delete SMS Event Flag from Authorized Phone Number – B03 .....	10
18.	Set Geo-fence Alarm – B05 .....	10
19.	Delete Geo-fence Waypoint – B06 .....	11
20.	Set Speeding Alarm – B07 .....	11
21.	Set Tow Alarm – B08 .....	12
22.	Set Extended Functions – B31 .....	12
23.	Set GPS Sleep Mode – B32 .....	12
24.	Set Power Down Mode – B33 .....	13
25.	Set Log Interval – B34 .....	13
26.	Time Zone Setting (for SMS Report) – B35 .....	13
27.	Time Zone Setting (for GPRS Report) – B36 .....	14
28.	Set SMS Header for Event – B91 .....	14
29.	Set Event Flag for GPRS Report – B92 .....	14
30.	Get Event Flag of GPRS Report – B93 .....	15
31.	Set Event Flag for Taking Picture – B96 .....	15
32.	Get Event Flag of Taking Picture – B97 .....	15
33.	Output Control – C01 .....	15
34.	Protocol Control – C03 .....	16
35.	Get Picture – D00 .....	16
36.	Get Picture List – D01 .....	16
37.	Delete Picture – D02 .....	17
38.	Take One Picture – D03 .....	17
39.	Get Firmware Version and SN – E91 .....	17
40.	Reboot GSM Module – F01 .....	17
41.	Reboot GPS Module – F02 .....	18
42.	Initialization – F11 .....	18
43.	Change Password – F20 .....	18
44.	Initialize Password – FAB .....	18
IV.	Annex 1: Description of GPRS/SMS Data .....	19
V.	Annex 2: Description of Event Code and SMS Header .....	20

File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	3 of 21
Revision:	V1.10	Confidential:	Internal Documentation

## I. Command Format

### 1. GPRS Format

From server to tracker:

@@<package flag><L>,<IMEI>,<command>,<data><\*checksum>\r\n

From tracker to server:

\$\$<package flag><L>,<IMEI>,<command>,<data><\*checksum>\r\n

Note:

‘,‘ is list separator in ASCII (0x2C);

Do not input ‘<‘ and ‘>‘ when writing a command;

All multi-byte data complies with the following sequence: High byte prior to low byte;

The size of a GPRS package (including data) is about 160 bytes.

Item	Definition
@@	2 bytes. Header of the package from server to tracker. It is in ASCII(0x40)
\$\$	2 bytes. Header of the package from tracker to server, It is in ASCII(0x24)
package flag	1 byte. In ASCII from 0x41 to 0x7A
L	Length from its following separator ‘,‘ to the ending character ‘\r\n’. It is decimal string. \$\$<package flag><L>,<IMEI>,<command>,<data><*checksum>\r\n
IMEI	Tracker’s IMEI which is normally 15 digitals.
command	Command code in Hex string. Please refer to the Command List and Command Details below.
data	Min 0 byte and max 160 bytes.
*	1 byte. A separator between data and checksum.
checksum	2 bytes. Indicating checksum of all data (not including checksum itself and the ending character). It is in HEX String. \$\$<package flag><L>,<IMEI>,<command>,<data><*checksum>\r\n
\r\n	2 bytes. Ending character in ASCII (0x0d,0x0a)

### 2. SMS Format

From mobile phone (or SMS modem) to tracker:

Password,<command>,<data>

From tracker to mobile phone (or SMS modem):

IMEI,<command>,< data>

Note:

Password is 4 digitals only and defaulted as 0000

Command is in HEX string. Please refer to the Command List and Command Details below.

File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	4 of 21
Revision:	V1.10	Confidential:	Internal Documentation

## II. Command List

Command	Definition	SMS/GPRS	Applicable Model
A00	Track on Demand	SMS	All
A01	Track on Demand - Google Map	SMS	All
A02	Track by Time Interval	SMS	All
A10	Track on Demand	GPRS	All
A11	Set Heartbeat Interval	GPRS	All
A12	Track by Time Interval	GPRS	All
A13	Heading Change Report	GPRS	All
A14	Track by Distance Interval	SMS/GPRS	All
A21	Set GPRS	SMS/GPRS	All
A22	Set DNS Server IP	SMS/GPRS	All
A23	Set Secondary GPRS Server	SMS/GPRS	All
AAA	Auto Event report	GPRS	All
AFF	Delete GPRS Event in Queue	GPRS	All
B00	Get Authorized Phone Number and SMS Event Flag	SMS/GPRS	All
B01	Authorize Phone Number and SMS Event Flag	SMS/GPRS	All
B02	Add SMS Event Flag to Authorized Phone Number	SMS/GPRS	All
B03	Delete SMS Event Flag from Authorized Phone Number	SMS/GPRS	All
B05	Set Geo-fence Alarm	SMS/GPRS	All
B06	Delete Geo-fence Waypoint	SMS/GPRS	All
B07	Set Speeding Alarm	SMS/GPRS	All
B08	Set Tow Alarm	SMS/GPRS	All
B31	Set Extended Functions	SMS/GPRS	All
B32	Set GPS Sleep Mode	SMS/GPRS	All
B33	Set Power Down Mode	SMS/GPRS	All
B34	Set Log Interval	SMS/GPRS	MT88, MVT100, 380, 600
B35	Time Zone Setting(For SMS Report)	SMS/GPRS	All
B36	Time Zone Setting(For GPRS Report)	SMS/GPRS	All
B91	Set SMS Header for Event	SMS/GPRS	All
B92	Set Event Flag for GPRS Report	GPRS	All
B93	Get Event Flag of GPRS Report	GPRS	All
B96	Set Event Flag for Taking Picture	GPRS	MVT600
B97	Get Event Flag of Taking Picture	GPRS	MVT600
C01	Output Control	SMS/GPRS	MVT100, 340, 380, 600
C03	Protocol Control	SMS/GPRS	All
D00	Get Picture	GPRS	MVT600
D01	Get Picture File Name	GPRS	MVT600
D02	Delete Picture	GPRS	MVT600
D03	Take One Picture	GPRS	MVT600
E91	Get Firmware Version and SN	SMS/GPRS	All
F01	Reboot GSM Module	SMS/GPRS	All
F02	Reboot GPS Module	SMS/GPRS	All
F11	Initialization	SMS/GPRS	All
F20	Change Password	SMS	All
FAB	Initialize Password	SMS	All

File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	5 of 21
Revision:	V1.10	Confidential:	Internal Documentation

### III. Command Details

#### 1. Track on Demand (SMS) – A00

SMS Set:	A00
SMS Get:	Now,<->yy.dddddd,<->xxx.dddddd,yyymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,Journey,Runtime,Base ID,State,AD,
Description:	Get the current location report of the tracker. Refer to Annex 1 for more information of data description.
Example	
SMS Tx:	1234,A00
SMS Rx:	353358017784062,Now,22.535888,114.063034,080310161834,A,9,27,30,179,0,15,8890,1346,,0000,,

#### 2. Track on Demand – Google Map (SMS) – A01

SMS Set:	A01
SMS Get:	<a href="http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1">http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1</a>
Description:	Get the current location report of the tracker and open the http link to Google Map to show the location on a mobile phone.
Example	
SMS Tx:	1234,A01
SMS Rx:	<a href="http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1">http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1</a>

#### 3. Track by Time Interval (SMS) – A02

SMS Set:	A02,interval,times
SMS Get:	A02,OK
Description:	interval =0, stop tracking by time interval (default); interval = [1,65535], track by interval in minute;  times = 0, track by interval continuously times = [1,255], set how many times(reports) of SMS from the tracker with the defined interval.
Example	
SMS Tx:	1234,A02,10,3
SMS Rx:	353358017784062,A02,OK <i>In this example, you can receive all 3 SMS with an interval of 10 minutes.</i> 353358017784062,Interval,22.542976,114.077658,100313092332,A,5,20,6,13,2,276,387,611,,0000,,



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	6 of 21
Revision:	V1.10	Confidential:	Internal Documentation

#### 4. Track on Demand (GPRS) – A10

GPRS Set:	A10
GPRS Get:	AAA,35,<->yy.dddddd,<->xxx.dddddd,yyymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude, Journey,Runtime,Base ID,State,AD,
Description:	35 is the GPRS code. Refer to Annex 2 for more information.
Example	
GPRS Tx:	@@Q25,353358017784062,A10*6A\r\n
GRRS Rx:	\$\$Q128,353358017784062,AAA,34,22.543176,114.078448,100313093738,A,5,22,2,205,5,-14, 0,60,0 0 10133 4110,0000,149 153 173 2707 914,*91\r\n

#### 5. Set Heartbeat Interval (GPRS) – A11

GPRS Set:	A11,interval
GPRS Get:	A11,OK
Description:	interval = 0, cancel heartbeat (default); interval = [1,65535], set interval in minute.
Example	
GPRS Tx:	@@S28,353358017784062,A11,10*FD\r\n
GRRS Rx:	\$\$S28,353358017784062,A11,OK*FE\r\n  <i>In this example, below message will be received every 10 minutes</i> \$\$a131,353358017784062,AAA,31,22.913458,114.083183,080229123628,A,9,23,21,83,1,18, 1350,127,0 0 10133 4110,0000,169 181 184 2714 919,*4B

#### 6. Track by Time Interval (GPRS) – A12

GPRS Set:	A12,interval,times
GPRS Get:	A12,OK
Description:	interval is in unit of 10 seconds. interval = 0, stop tracking by time interval. Max time interval = 65535*10 seconds  times = 0, track by interval continuously; times = [1,65535], set how many times(reports) from the tracker with the specified interval.
Example	
GPRS Tx:	@@V29,353358017784062,A12,6,3*36\r\n
GRRS Rx:	\$\$V28,353358017784062,A12,OK*02\r\n  <i>In this example, below message will be received every minute and total is 3 messages to be received.</i> \$\$W129,353358017784062,AAA,35,22.540113,114.076141,100313094354,A,5,22,1,174,4,12 9,0,435,0 0 10133 4110,0000,166 224 193 2704 916,*BE\r\n



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	7 of 21
Revision:	V1.10	Confidential:	Internal Documentation

### 7. Heading Change Report (GPRS) – A13

GPRS Set:	A13,degree
GPRS Get:	A13,OK
Description:	When the heading direction of the tracker changes over the preset degree, a message with location data will be sent back to the server by GPRS. degree = 0, cancel heading change report (default); degree = [1,359], set degree of direction change.
Example	
GPRS Tx:	@@X29,353358017784062,A13,120*37\r\n
GRRS Rx:	\$\$X28,353358017784062,A13,OK*05\r\n  <i>In this example, below data will be received when heading changes over 120 degree</i> \$\$Y129,353358017784062,AAA,32,22.540968,114.077455,100313094534,A,4,22,1,166,3,175, 0,534,0 0 10133 4110,0000,141 138 159 2691 904,*D9\r\n

### 8. Track by Distance Interval – A14

SMS/GPRS Set:	A14,distance
SMS/GPRS Get:	A14,OK
Description:	distance = 0, stop tracking by distance interval (default); distance = [1, 4294967295], set interval in meter
Example	
SMS Tx:	1234,A14,1000
SMS Rx:	353358017784062,A14,OK  <i>In this example, below message will be received once distance changes over 1000 meters.</i> 353358017784062,Distance,22.547278,114.047723,080310080934,A,7,21,30,88,1,12,8525,56 3,,0000,,
GPRS Tx:	@@D30,353358017784062,A14,1000*4A\r\n
GRRS Rx:	\$\$D28,353358017784062,A14,OK*F2\r\n  <i>In this example, below message will be received once distance changes over 1000 meters.</i> \$\$D131,353358017784062,AAA,33,22.547271,114.047405,080310080929,A,8,21,13,89,1,12, 8525,561,0 0 10133 4110,0000,163 185 186 2712 939,*31\r\n

### 9. Set GPRS – A21

SMS/GPRS Set:	A21,X,IP,Port,APN,APN username,APN password
SMS/GPRS Get:	A21,OK
Description:	X = 0, close GPRS; X = 1, open TCP; X = 2, open UDP.  IP : IP address or domain name, max 32 bytes.



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	8 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	Port: max 5 bytes.
	APN / APN username / APN password: max 32 bytes; If no username and password required, leave them blank.
Example	
SMS Tx:	1234,A21,1,meitrack.com,8056,CMNET,,
SMS Rx:	353358019687743,A21,OK
GPRS Tx:	@@H53,353358019687743,A21,1,meitrack.com,8056,CMNET,*,*AE\r\n
GRRS Rx:	\$\$H28,353358019687743,A21,OK*FE\r\n

#### 10. Set DNS Server IP – A22

SMS/GPRS Set:	A22,DNS Server IP
SMS/GPRS Get:	A22,OK
Description:	In case the domain name you set by the command A21 doesn't work, which means your server IP is not properly set. You can first use this command to set DNS Server IP (please check with your DNS server provider for the DNS Server IP) and then redo the command A21.  DNS Server IP: max 16 bytes
Example	
SMS Tx:	1234,A22,202.1.2.30
SMS Rx:	353358019687743,A22,OK
GPRS Tx:	@@K38,353358019687743,A22,75.127.67.90*07\r\n
GRRS Rx:	\$\$K28,353358019687743,A22,OK*02\r\n

#### 11. Set Secondary GPRS Server – A23

SMS/GPRS Set:	A23,IP,Port
SMS/GPRS Get:	A23,OK
Description:	IP : max 32 bytes Port: max 5 bytes
Example	
SMS Tx:	1234,A23,meiligao.net,8056
SMS Rx:	353358019687743,A23,OK
GPRS Tx:	@@S43,353358019687743,A23,meiligao.net,8056*61\r\n
GRRS Rx:	\$\$S28,353358019687743,A23,OK*0B\r\n

#### 12. Auto Event Report – AAA

GPRS Get:	AAA,Code, <->yy.dddddd,<->xxx.dddddd,yyymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,Journey, Runtime,Base ID,State,AD,
Description:	Unsolicited GPRS event report
Example	
GRRS Rx:	<i>If the SOS button on the tracker is pressed, the following report will be received.</i>





File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	9 of 21
Revision:	V1.10	Confidential:	Internal Documentation

\$\$G127,353358017784062,AAA,1,22.538169,114.075958,100313095653,A,3,21,4,46,5,581,0,148,0|0|10133|4172,0000,166|204|205|2709|878,\*77\r\n

### 13. Delete GPRS Event in Queue Buffer – AFF

GPRS Set:	AFF,sum to delete
GPRS Get:	AFF,sum of balance,Code,<->yy.dddddd,<->xxx.dddddd,yyymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,Journey,Runtime,Base ID,State,AD,
Description:	sum to delete: HEX string and normally is 1. Sum of balance: HEX string. Total number of events in memory.
Example	
GPRS Tx:	@@h27,353358017028395,AFF,1*0B\r\n
GRRS Rx:	

### 14. Get Authorized Phone Number and SMS Event Flag – B00

SMS/GPRS Set:	B00,P
SMS/GPRS Get:	B00,P,Phone No,Event Code
Description:	P: 1 to 3 Phone No: max 16 characters. If Phone No is blank, no phone number is authorized. Event Code: 16+8 bytes, HEX String. See Annex 2 for more details
Example	
SMS Tx:	1234,B00,1
SMS Rx:	353358019687743,B00,1,13612345678,0000000000000F0A00000000
GPRS Tx:	@@H27,353358019687743,B00,1*CA\r\n
GRRS Rx:	\$\$H64,353358019687743,B00,1,13420980279,00000000201C001F00000060*DB\r\n

### 15. Authorize Phone Number and SMS Event Flag – B01

SMS/GPRS Set:	B01,P,Phone No,Event Code
SMS/GPRS Get:	B01,OK
Description:	P: 1 to 3 Phone No: max 16 characters. Event Code: If no codes stipulated, then it will apply the default flags to the authorized phone number. See Annex 2 for more details of Event Code and default settings.
Example	
SMS Tx:	1234,B01,1,13612345678,1
SMS Rx:	353358017784062,B01,OK
GPRS Tx:	@@Z41,353358017784062,B01,1,13420980279,1*95\r\n
GRRS Rx:	\$\$Z28,353358017784062,B01,OK*05\r\n
	<i>In this example, once the SOS button is pressed, the following message will be received.</i> 353358017784062,SOS,22.540768,114.077610,100313100055,A,3,21,1,94,5,255,0,381,,0000,,



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	10 of 21
Revision:	V1.10	Confidential:	Internal Documentation

#### 16. Add SMS Event Flag to Authorized Phone Number – B02

SMS/GPRS Set:	B02,P,Event Code
SMS/GPRS Get:	B02,OK
Description:	P : 1 to 3 Event Code: please refer to Annex 2 for more details.
Example	
SMS Tx:	1234,B02,1,17
SMS Rx:	353358017784062,B02,OK
GPRS Tx:	@@]30,353358017784062,B02,1,17*65\r\n
GRRS Rx:	\$\$]28,353358017784062,B02,OK*09\r\n
<i>In this example, the low battery alarm message will be received when the battery is low.</i>	

#### 17. Delete SMS Event Flag from Authorized Phone Number – B03

SMS/GPRS Set:	B03,P,Event Code
SMS/GPRS Get:	B03,OK
Description:	P : 1 to 3 Event Code: please refer to Annex 2 for more details. If no Event code input, it will remove all event flags from the authorized phone number.
Example	
SMS Tx:	1234,B03,1,17
SMS Rx:	353358017784062,B03,OK
GPRS Tx:	@@F30,353358017784062,B03,1,17*4F\r\n
GRRS Rx:	\$\$F28,353358017784062,B03,OK*F3\r\n
<i>This is to cancel low battery alarm.</i>	

#### 18. Set Geo-fence Alarm – B05

SMS/GPRS Set:	B05,P,latitude,longitude,radius,in,out
SMS/GPRS Get:	B05,OK
Description:	P: 1 to 8. Max 8 Geo-fence waypoints can be set. Latitude: Latitude in decimal degrees of the waypoint center. Longitude: Longitude in decimal degrees of the waypoint center. Radius: [1, 4294967295] in meters. In = 0, turn off the alarm when the tracker enters the waypoint; In = 1, turn on the alarm when the tracker enters the waypoint. Out = 0, turn off the alarm when the tracker exits the waypoint; Out = 1, turn on the alarm when the tracker exits the waypoint.
Example	
SMS Tx:	1234,B05,1,22.91319,114.07988,1000,0,1
SMS Rx:	353358017784062,B05,OK



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	11 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	<p>Once the tracker go outside of the circle (center: 22.91319,114.07988 and radius 1000 meters), the following message will be received.</p> <p>353358017784062,ExitGEO,22.918186,114.089823,080229123816,A,10,22,16,32,1,21,6667,850,,0000,,</p>
GPRS Tx:	@@H55,353358017784062,B05,1,22.91319,114.07988,1000,0,1*31\r\n
GRRS Rx:	<p>\$\$H28,353358017784062,B05,OK*F7\r\n</p> <p>Once the tracker go outside of the circle (center: 22.91319,114.07988 and radius 1000 meters), the following message will be received.</p> <p>\$\$J132,353358017784062,AAA,21,22.918046,114.089726,080229123812,A,10,22,12,32,1,21,6667,847,0 0 10133 4110,0000,124 181 183 2714 922,*5A\r\n</p>

#### 19. Delete Geo-fence Waypoint – B06

SMS/GPRS Set:	B06,P
SMS/GPRS Get:	B06,OK
Description:	P: 1 to 8. Only one waypoint can be deleted by each SMS/GPRS command.
Example	
SMS Tx:	1234,B06,1
SMS Rx:	353358017784062,B06,OK
GPRS Tx:	@@J27,353358017784062,B06,1*C8\r\n
GRRS Rx:	<p>\$\$J28,353358017784062,B06,OK*FA\r\n</p> <p>In this example, the first predefined waypoint is deleted.</p>

#### 20. Set Speeding Alarm – B07

SMS/GPRS Set:	B07,speed
SMS/GPRS Get:	B07,OK
Description:	Speed = 0, cancel speeding alarm (default) Speed = [1,255], set speed limit in Km/h
Example	
SMS Tx:	1234,B07,60
SMS Rx:	353358017784062,B07,OK
	<p>In this example, the following message will be received one the tracker's speed is over 60km/h.</p> <p>353358017784062,Speeding,22.914891,114.087491,080229203703,A,10,22,55,44,1,24,6635,388,,0000,,</p>
GPRS Tx:	@@P28,353358017784062,B07,60*05\r\n



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	12 of 21
Revision:	V1.10	Confidential:	Internal Documentation

GRRS Rx:	<pre>\$\$P28,353358017784062,B07,OK*01\r\n</pre> <p><i>In this example, the following message will be received one the tracker's speed is over 60km/h.</i></p> <pre>\$\$k134,353358017784062,AAA,19,22.916675,114.088813,080229123718,A,10,22,61,31,1,21,6635,395,460 0 10133 4110,0000,164 185 181 2712 915,*F7\r\n</pre>
----------	--

### 21. Set Tow Alarm – B08

SMS/GPRS Set:	B08,time
SMS/GPRS Get:	B08,OK
Description:	time = 0, cancel tow alarm (default); time = [1,255], set period in second.
Example	
SMS Tx:	1234,B08,3
SMS Rx:	353358017028395,B08,OK
	<p><i>In this example, when the tracker moves or trembles for over 3 seconds, the following message will be received.</i></p> <pre>Tow,&lt;-&gt;yy.ddddd,&lt;-&gt;xxx.ddddd,ymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,Journey,Runtime,Base ID,State,AD,</pre>
GPRS Tx:	@@I27,353358019687743,B08,3*D5\r\n
GRRS Rx:	<pre>\$\$I28,353358019687743,B08,OK*05\r\n</pre> <p><i>In this example, when the tracker moves or tremble for over 3 seconds, the following message will be received.</i></p> <pre>AAA,36,&lt;-&gt;yy.ddddd,&lt;-&gt;xxx.ddddd,ymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,Journey,Runtime,Base ID,State,AD,</pre>

### 22. Set Extended Functions – B31

SMS/GPRS Set:	B31,AB
SMS/GPRS Get:	B31,OK
Description:	A=0, all LED lights work normally (default). A=1, all LED lights are off when the tracker is working. B, reserved.
Example	
SMS Tx:	1234,B31,11
SMS Rx:	353358019687743,B31,OK
GPRS Tx:	@@J28,353358019687743,B31,10*01\r\n
GRRS Rx:	<pre>\$\$J28,353358019687743,B31,OK*02\r\n</pre>

### 23. Set GPS Sleep Mode – B32

SMS/GPRS Set:	B32,level
SMS/GPRS Get:	B32,OK
Description:	level = 0, cancel sleep mode (default)



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	13 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	level = 1, GPS module works for 3 minutes and close for 1 minute. level = 2, GPS module works for 1 minute and close 2 minutes.
Example	
SMS Tx:	1234,B32,1
SMS Rx:	353358019687743,B32,OK
GPRS Tx:	@@L27,353358019687743,B32,1*D3\r\n
GRRS Rx:	\$\$L28,353358019687743,B32,OK*05\r\n

#### 24. Set Power Down Mode – B33

SMS/GPRS Set:	B33,minute
SMS/GPRS Get:	B33,OK
Description:	Set power down mode when the tracker is inactive (stationary) for a period of time. In Power Down mode, GPS stops working and GSM enters sleep and stop sending out message until it is activated by message, incoming calls, movement or input changes. minute = 0, turn off power down mode minute = [1,255], turn on power down after a specified period of being inactive in minute.
Example	
SMS Tx:	1234,B33,3
SMS Rx:	353358019687743,B33,OK  <i>In this example, the tracker will enter power down mode after it is inactive for 3 minutes.</i>
GPRS Tx:	@@M27,353358019687743,B33,3*D7\r\n
GRRS Rx:	\$\$M28,353358019687743,B33,OK*07\r\n

#### 25. Set Log Interval – B34

SMS/GPRS Set:	B34,interval
SMS/GPRS Get:	B34,OK
Description:	Set the interval for storing GPS data into tracker's flash memory. interval = 0, turn off logging; interval = [1,65535], set logging interval in second.
Example	
SMS Tx:	1234,B34,60
SMS Rx:	353358019687743,B34,OK
GPRS Tx:	@@N28,353358019687743,B34,60*0D\r\n
GRRS Rx:	\$\$N28,353358019687743,B34,OK*09\r\n

#### 26. Time Zone Setting (for SMS Report) – B35

SMS/GPRS Set:	B35,minute
SMS/GPRS Get:	B35,OK
Description:	Default time of the tracker is GMT, you can use this comment to correct it to your local time for SMS report. minute = 0, GMT (default);



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	14 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	minute = [-32768,32767], set time difference in minute to GMT.
Example	
SMS Tx:	1234,B35,-480
SMS Rx:	353358019687743,B35,OK
GPRS Tx:	@@O29,353358019687743,B35,480*46\r\n
GRRS Rx:	\$\$O28,353358019687743,B35,OK*0B\r\n

### 27. Time Zone Setting (for GPRS Report) – B36

SMS/GPRS Set:	B36,minute
SMS/GPRS Get:	B36,OK
Description:	minute = 0, GMT (default); minute = [-32768,32767], set time difference in minute to GMT.
Example	
SMS Tx:	1234,B36,-480
SMS Rx:	353358019687743,B36,OK
GPRS Tx:	@@P29,353358019687743,B36,480*48\r\n
GRRS Rx:	\$\$P28,353358019687743,B36,OK*0D\r\n

### 28. Set SMS Header for Event – B91

SMS/GPRS Set:	B91,Event Code,Header
SMS/GPRS Get:	B91,OK
Description:	Header: max 16 bytes. Please refer to Annex 2 for more details
Example	
SMS Tx:	1234,B91,1,SOS
SMS Rx:	353358019687743,B91,OK
GPRS Tx:	@@R31,353358019687743,B91,1,SOS*FA\r\n
GRRS Rx:	\$\$R28,353358019687743,B91,OK*10\r\n
	<i>After the SOS button(input1) is pressed, it shows 'SOS' in the beginning of the alarm message.</i>

### 29. Set Event Flag for GPRS Report – B92

GPRS Set:	B92,Event Code Flag
GPRS Get:	B92,OK
Description:	Set one or more event flag to the GPRS report. Please refer to Annex 2 for more details of the Event Code. Default authorized codes are stipulated in Annex 2.
Example	
GPRS Tx:	@@q42,353358019687743,B92,1234567890ABCDEF*6C\r\n
GRRS Rx:	\$\$q28,353358019687743,B92,OK*30\r\n



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	15 of 21
Revision:	V1.10	Confidential:	Internal Documentation

### 30. Get Event Flag of GPRS Report – B93

GPRS Set:	B93
GPRS Get:	B93,Event Flag
Description:	Read the preset event code of GPRS report.
Example	
GPRS Tx:	@@V25,353358019687743,B93*85\r\n
GRRS Rx:	\$\$V42,353358019687743,B93,00000007E01C001F*BF\r\n

### 31. Set Event Flag for Taking Picture –B96

GPRS Set:	B96,Event Code Flag
GPRS Get:	B96,OK
Description:	Set one or more events to take picture. Once each event is activated, the camera takes picture and store the image in memory.  In default mode, once the SOS button is pressed, the tracker will automatically take picture and store it in memory.  Please refer to Annex 2 for more details of the Event Code.
Example	
GPRS Tx:	@@A42,356895034353592,B96,0000000000000001*9D\r\n
GRRS Rx:	\$\$A28,356895034353592,B96,OK*02\r\n

### 32. Get Event Flag of Taking Picture –B97

GPRS Set:	B97
GPRS Get:	B97,Event Flag
Description:	To know which event(s) have been enabled the function of taking pictures.
Example	
GPRS Tx:	@@C25,356895034353592,B97*74\r\n
GRRS Rx:	\$\$C42,356895034353592,B97,0000000000000001*68\r\n

### 33. Output Control – C01

SMS/GPRS Set:	C01, speed,ABCDE
SMS/GPRS Get:	C01,OK
Description:	Speed = 0, no speed limit Speed = [1,255], in km/h, set conditional speed limit for output control. When speed is below the set speed, output is activated. A=0, close output (OUT1) -open drain A=1, open output (OUT1) -connect to GND A=2, remain previous status. B=0, close output (OUT2) -open drain B=1, open output (OUT2) -connect to GND B=2, remain previous status. C=0, close output (OUT3) -open drain



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	16 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	<p>C=1, open output (OUT3) -connect to GND</p> <p>C=2, remain previous status.</p> <p>D=0, close output (OUT4) -open drain</p> <p>D=1, open output (OUT4) -connect to GND</p> <p>D=2, remain previous status.</p> <p>E=0, close output (OUT5) -open drain</p> <p>E=1, open output (OUT5) -connect to GND</p> <p>E=2, remain previous status.</p>
Example	
SMS Tx:	1234,C01,80,12221
SMS Rx:	353358019687743,C01,OK
GPRS Tx:	@@M35,353358019687743,C01,20,101222*55\r\n
GRRS Rx:	\$\$M28,353358019687743,C01,OK*03\r\n

#### 34. Protocol Control – C03

SMS/GPRS Set:	C03, X
SMS/GPRS Get:	C03,OK
Description:	<p>X = 0, Auto Event Report (default)</p> <p>X = 1, Event report needs server's confirmation by AFF command</p>
Example	
SMS Tx:	1234,C03,0
SMS Rx:	353358019687743,C03,OK
GPRS Tx:	@@f27,353358017784062,C03,0*E1\r\n
GRRS Rx:	\$\$f28,353358017784062,C03,OK*14\r\n

#### 35. Get Picture – D00

GPRS Set:	D00, File Name,Index
GPRS Get:	D00, File Name,Total,Index,Data
Description:	<p>File Name: The file name of the picture you want to get from tracker's memory.</p> <p>Index: Sequence number of the package. Min = 0</p> <p>Total: Total number of the packages. Min = 1</p> <p>Data: Date of the picture taken.</p>
Example	
GPRS Tx:	@@O48,356895034353592,D00,0215080432_C2E03.jpg,0*E3\r\n
GRRS Rx:	\r\n

#### 36. Get Picture List – D01

GPRS Set:	D01, Index
GPRS Get:	D01, Total,Index,File(1) File(2) ...File(n)
Description:	<p>File(n): File name of the pictures separated by ' '. Index: Sequence number of the picture. Min = 0. For example, if Index = 0, the file names received will start from the 1st picture and if Index = 4, the file name will start from the 5th</p>





File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	17 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	picture. Total: Total number of pictures. Min = 1.
Example	
GPRS Tx:	@@A27,356895034353592,D01,0*C3\r\n
GRRS Rx:	\$\$A480,356895034353592,D01,3,0,0506162517_C1E03.jpg 0506162517_C1E11.jpg 0506162624_C1E03.jpg 0506162630_C1E11.jpg 0506162720_C1E03.jpg 0506162721_C1E03.jpg 0215080547_C1E03.jpg 0215080547_C1E11.jpg 0215080626_C1E03.jpg 0215080626_C1E11.jpg 0215080827_C1E03.jpg 0215080827_C1E11.jpg 0215080850_C1E03.jpg 0215080850_C1E11.jpg 0507145426_C1E03.jpg 0507145426_C1E11.jpg 0507145512_C2E03.jpg 0507145512_C2E11.jpg 0215080050_C3E03.jpg 0215080050_C3E11.jpg 0215080459_C3E03.jpg 021508050*49\r\n

### 37. Delete Picture – D02

GPRS Set:	D02, File(1) File(2) ...File(n)
GPRS Get:	D02,OK
Description:	File(n): File name of picture(s) you want to delete. Separated by ' '. Example
GPRS Tx:	@@E110,356895034353592,D02,0506162517_C1E03.jpg 0506162517_C1E11.jpg 0506162624_C1E03.jpg 0506162630_C1E11.jpg *56\r\n
GRRS Rx:	\$\$F28,356895034353592,D02,OK*FC\r\n

### 38. Take One Picture – D03

GPRS Set:	D03,Index,File Name,
GPRS Get:	D03, OK
Description:	Index: camera number. Min = 1 File Name: The file name of the picture. Example
GPRS Tx:	@@D46,356895034353592,D03,1,camera picture.jpg*EA\r\n
GRRS Rx:	\$\$D28,356895034353592,D03,OK*FB\r\n

### 39. Get Firmware Version and SN – E91

SMS/GPRS Set:	E91
SMS/GPRS Get:	E91,Version,SN
Description:	Get current firmware version and S/N details of the tracker. Example
SMS Tx:	1234,E91
SMS Rx:	353358019687743,E91,FWV1.00,12345678
GPRS Tx:	@@W25,353358019687743,E91*87\r\n
GRRS Rx:	\$\$W38,353358019687743,FWV1.00,12345678*26\r\n

### 40. Reboot GSM Module – F01

SMS/GPRS Set:	F01
SMS/GPRS Get:	F01,OK



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	18 of 21
Revision:	V1.10	Confidential:	Internal Documentation

Description:	Reboot GSM module
Example	
SMS Tx:	1234,F01
SMS Rx:	353358017784062,F01,OK
GPRS Tx:	@@j25,353358017784062,F01*88\r\n
GRRS Rx:	\$\$j28,353358017784062,F01,OK*19\r\n

#### 41. Reboot GPS Module – F02

SMS/GPRS Set:	F02
SMS/GPRS Get:	F02,OK
Description:	Reboot GPS Module
Example	
SMS Tx:	1234,F02
SMS Rx:	353358019687743,F02,OK
GPRS Tx:	@@Z25,353358019687743,F02*83\r\n
GRRS Rx:	\$\$Z28,353358019687743,F02,OK*14\r\n

#### 42. Initialization– F11

SMS/GPRS Set:	F11
SMS/GPRS Get:	F11,OK
Description:	Make all parameters (except for the password) back to factory default.
Example	
SMS Tx:	1234,F11
SMS Rx:	353358019687743,F11,OK
GPRS Tx:	@@[25,353358019687743,F11*84\r\n
GRRS Rx:	\$\$[28,353358019687743,F11,OK*15\r\n

#### 43. Change Password – F20

SMS Set:	F20,New Password
SMS Get:	F20,OK
Description:	Change SMS password. Password is 4 digits.
Example	
SMS Tx:	0000,F20,1234
SMS Rx:	353358019687743,F20,OK

#### 44. Initialize Password – FAB

SMS Set:	8888,FAB
SMS Get:	FAB,OK
Description:	Make the password back to factory default in case you forget your password. Only authorized phone number(s) can send this command.
Example	
SMS Tx:	8888,FAB



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	19 of 21
Revision:	V1.10	Confidential:	Internal Documentation

SMS Rx:	353358019687743,FAB,OK
---------	------------------------

## IV. Annex 1: Description of GPRS/SMS Data

Date in each GPRS/SMS message from the tracker includes:

Code(or SMS Header),<->yy.dddddd,<->xxx.dddddd,yyymmddHHMMSS,Z,N,G,Speed,Heading,HDOP,Altitude,  
Journey,Runtime,Base ID,State,AD,RFID

Details:

Parameter	Description	Example
<b>Code</b>	Event code Refer to Annex 2 for more details	1
<b>SMS String</b>	Refer to Annex 2 for more details	SOS
<b>&lt;-&gt;yy.dddddd</b>	Latitude: in unit of degree '-' is south, none is north yy = degrees; dddddd = decimal part of degree	22.756325 -23.256438
<b>&lt;-&gt;xxx.dddddd</b>	Longitude: in unit of degree '-' is west, none is east xxx = degrees; dddddd = decimal part of degree	114.752146 -114.821453
<b>yyymmddHHMMSS</b>	yy = year mm = month dd = date HH = hours MM = minutes SS = seconds	091221102631
<b>Z</b>	GPS status indicator: A = valid, V = invalid	A = Valid
<b>N</b>	Numbers of satellites available	5
<b>G</b>	GSM signal	0~31
<b>Speed</b>	Km/h	58
<b>Heading</b>	Heading, in unit of degree	275
<b>HDOP</b>	Horizontal Dilution of Precision, 0.5-99.9. HDOP is blank when no GPS fix.	5
<b>Altitude</b>	MSL Altitude, in unit of meter.	118
<b>Journey</b>	In unit of meter, decimal string	564870
<b>Runtime</b>	In unit of second, decimal string	2546321
<b>Base ID</b>	ID of the base station including MCC MNC LAC CI	460 0 E166 A08B



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	20 of 21
Revision:	V1.10	Confidential:	Internal Documentation

	Note: for SMS report, the Base ID is empty. LAC and CI is Hex string	
<b>State</b>	Status of input and output	0000(HEX String)
<b>AD</b>	Separated by ' ' Note: for SMS report, AD is empty.	123 456 235 1234 324  654 1456 222(HEX String)
<b>RFID</b>	IC Card identity code, decimal string Only shown in GPRS Event Code 37	42770680(HEX String)

## V. Annex 2: Description of Event Code and SMS Header

Event Code	Event	Default SMS Header (max 16 bytes)	Default GPRS Flag	Default SMS Flag	Default Picture Flag
1	Input 1 Active	SOS	Y	Y (Only for the first authorized phone number)	Y
2	Input 2 Active	In2	Y	N	N
3	Input 3 Active	In3	Y	N	N
4	Input 4 Active	In4	Y	N	N
5	Input 5 Active	In5	Y	N	N
9	Input 1 Inactive		N	N	N
10	Input 2 Inactive		N	N	N
11	Input 3 Inactive		N	N	N
12	Input 4 Inactive		N	N	N
13	Input 5 Inactive		N	N	N
17	Low Battery	Low Battery	N	N	N/A
18	Low External Power	Low Power	N	N	N/A
19	Speeding	Speeding	Y	Y	N
20	Enter Geo-fence	Enter GEO	Y	Y	N
21	Exit Geo-fence	Exit GEO	Y	Y	N
22	External Power On	Power On	N	N	N
23	External Power Off	Power Off	N	N	N/A
24	No GPS Signal	No Fix	N	N	N/A
25	Get GPS Signal	Fix	N	N	N/A
26	Enter Sleep	Enter Sleep	N	N	N/A
27	Exit Sleep	Exit Sleep	N	N	N/A
28	GPS Antenna Cut	Antenna Cut	N	N	N
29	Device Reboot	Reboot	N	N	N/A
30	Impact	Impact	Y	N	N
31	Heartbeat Report	(only for GPRS)	Y	N/A	N/A



File Name:	MEITRACK GPRS/SMS Protocol	Creator:	Cavana Cheung
Project:	MVT340/MVT380/MVT100/ MVT600/MT88	Creation Date:	2010-03-25
Sub Project:	GPRS/SMS Protocol	Page:	21 of 21
Revision:	V1.10	Confidential:	Internal Documentation

32	Heading Change Report	Heading Change	Y	N	N/A
33	Distance Interval Report	Distance	Y	N	N/A
34	Current Location Report	Now	A/A	A/A	N/A
35	Time Interval Report	Interval	A/A	A/A	N/A
36	Tow Alarm	Tow	Y	N	N
37	RFID	(only for GPRS)	Y	N/A	N
65	Press Input 1 (SOS) to Call	/	N/A	N	N/A
66	Press Input 2 to Call	/	N/A	N	N/A
67	Press Input 3 to Call	/	N/A	N	N/A
68	Press Input 4 to Call	/	N/A	N	N/A
69	Press Input 5 to Call	/	N/A	N	N/A
70	Reject Incoming Call	/	N/A	Y	N/A
71	Report Location after Calling in	/	N/A	Y	N/A
72	Auto Answer Incoming Call	/	N/A	N	N/A
73	Listen-in (voice monitoring)	/	N/A	N	N/A

Note:

1. Above figures are the factory default settings.
2. **Y** = yes; **N** = no; **N/A** = not applicable or not available; **A/A** = always stay available in all states and cannot be changed.
3. You can use commands to define SMS header, add and delete flag for each function.